Customer: F	Project:		Page:of
Pair Opening Quote/Order Form (this form is NOT required to request a quote or to place an order) Osprey FRP Door			
Croy Boigo Blowing	Only Both Dark Primer	NOTE: Please indicate o width and 1 height meast on the diagram. We'll cal the rest from there.	urement
Fire Rating: 90M 60M 45M 20	— Custom ⊢	Rough Opening	
Standard Jamb Profiles	_	Frame OA	
5-3/4" 5-3/4" 5-3/4" 4-7/6"		Frame Net Width Actual Door Width Actual Door Width	
Jamb Faces: 2" Other	n Opening		
Head Face: 2" 4"	Frame OA		4111
KD (Pairs ship KD)			
EWA-Masonry Wire EWA-Tapcon New Stud Wall		C/L of Lock/Strike	
EWA-Wood lag	Frame Net Height		
Cutout #1 Both Doors Width Height	Actual Door Size	Other Undercut	
Visible Order Size		Std Under	
Centered or Side Margin:	Finished Floor		
Top Margin (lite) Bottom Margin (louver)	Approved Hardware S	Schedule Attached Manuf	Locations
Type: Tempered Polycarb		Schedule Attached Manuf	
"V" Louver By Others	Cylinder Lock:		
Thickness: 1/4" 1" (Insul)	Deadbolt:		
Cutout Only By Others		Trim:	
Cutout #2 Both Doors	Flush/Surface Bolts:		
Width Height	Notes/Other:		
Visible Order Size			
Centered or Side Margin:	Quantity Handing Ta	g #	
Top Margin (lite)			<u> </u>
Bottom Margin (louver) Type: Tempered Polycarb			
"V" Louver By Others			
	- 		_
Thickness: 1/4" 1" (Insul) L Cutout Only			